

Technical Data Sheet
Issued, 26.03.2015

FB 5-021 F02 Rev. 1



DINITROL 6110

Megafill Spray

Characteristics:

DINITROL 6110 Megafill Spray is an acrylic resin-based filler in aerosol packaging. The product has excellent filling properties, dries quickly, is easy to file and can be used with most repair lacquers.

Areas of Application:

DINITROL 6110 Megafill Spray is used to level scratches, scrapes and other minor damage to paintwork.

Method of Use:

The surface to be treated must be clean and free from oil and grease. File all surrounding edges with fine sandpaper. Cover all areas which are not to be treated. Shake the can well before use (1 – 2 minutes), until the mixing ball can clearly be heard. Spray at a distance of 20 – 30 cm. Spray DINITROL 6110 Megafill in a cross coat. For small surfaces, the product can also be sprayed in a circular movement. If required, repeat the process after the former coat is dry. In order to prevent any nozzle blockages, hold the can downwards after use and briefly spray pure gas. Once dry, DINITROL 6110 Megafill Spray can be filed and painted. If the filler is applied in a fine layer as a primer, the surface need not be filed before painting. Depending on temperature, humidity and coat thickness, the product is touch-dry after approx. 20 – 30 minutes.

Technical data:

Base:	Acrylic resin
Colour:	grey
Density:	0.82 g/cm ³
Propellant:	Propane/butane
Drying time until filing:	approx. 25 mins – 20°C
Drying 60°C:	10 min.
Storage time:	12 months (between 15° and 25°)
Package size:	400 ml

Note: Opened packages must be used as quickly as possible.

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmont Str. 76
D-32676 Lügde
Telephone:
+49 (0) 52 81 / 9 82 98-0
Fax:
+49 (0) 52 81 / 9 82 98-60
Email:
service@dinol.com