

DINITROL® 19

Universal Protection

Characteristics:

- Transparent
- Extremely thin film
- Very easy to remove
- Dipping application
- Short term storage
- For use in between process steps

Applications:

DINITROL 19 has excellent water removal properties and dries very quickly. DINITROL 19 is designed to protect iron and steel parts in the interim between different production operations and during short periods of storage indoors, in particular when the parts are wetted by e.g. rinsing water, cutting oil emulsions etc. DINITROL 19 provides excellent corrosion protection indoors at extremely low film thickness.

Method of use:

DINITROL 19 is best applied by dipping. The most rapid way of repelling the water is by a light shaking of the dipped parts in the corrosion preventive. In cases where the waterrepellent power is of minor importance, DINITROL 19 may be applied by brushing or spraying. Spraying may be undertaken by using either airless or airmix type of equipment.

Technical properties:

Colour:	Transparent
Type of film:	Greasy
Density at 23°C:	780 kg/m ³
Flash point:	40°C
Rec. film thickness:	0.03 µm
Drying time:	1 hr
Effect on car paint:	None
Low temperature adhesion:	- 40°C
Available in:	208 L Drum

For all relevant safety advices please read the material safety data sheet or the packaging label.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Telefon:
+49 (0) 52 81 / 9 82 98-0
Telefax:
+49 (0) 52 81 / 9 82 98-60
E-Mail:
service@dinol.com