



V.1.3 GB
REV 08.01.2016.

High Performance Coatings

Q-Line® 690B

(For professional use only)

Technical Datasheet



www.qlinedirect.com



Logistics & Technical: Eagle House | Eagle Park Drive | Warrington | Cheshire | WA2 8JA | United Kingdom
t. +44 (0) 1925 241250 | f. +44 (0) 1925 520210 | e. info@big-internationalgroup.com





V.1.3 GB
REV 08.01.2016.

High Performance Coatings

TDS

Colour/Type	Blue, Black / Under body and stone chip coating
Areas of usage:	Chassis, wheel-housings and side-skirts of cars, trucks and coaches
Environment:	100% VOC FREE, Hazardous for water, Please refer to MSDS
Packaging:	20 - 60 - 208 Litre containers
PPE:	Wear respirator mask and gloves. Avoid skin contact Refer to MSDS & COSHH
Storage:	1 year in the unopened original packaging or until expire date Min/Max temp +10/+30. Protect from direct sunlight & heat
Surface prep:	Clean dust and grease free
Equipment needed:	Airless spray equipment and a pressure of 2-4 bar with 317 Tip.
Tests:	ISO9001. (For further information contact B.I.G International LTD)
Applying/Drying:	Shake before use or stir the product thoroughly
Origin/Manufacture:	B.I.G International NV (Netherlands)



www.qlinedirect.com



Logistics & Technical: Eagle House | Eagle Park Drive | Warrington | Cheshire | WA2 8JA | United Kingdom
t. +44 (0) 1925 241250 | f. +44 (0) 1925 520210 | e. info@big-internationalgroup.com





V.1.3 GB
REV 08.01.2016.

High Performance Coatings

Useful Information

How to optimise the use of Q-Line® 690B

Applications:

Q-Line® 690B is a 100% VOC FREE, environmentally friendly bitumen based under body and stone chip coating with corrosion protection and sound deadening properties. After curing Q-Line® 690B has a very durable tough and elastic film, defending the coated surface against aggressive chemicals and atmospheric, pollution and weathering. Q-Line® 690B can be applied as an anti corrosion protection across a vast amount of areas including the automotive industry, bus & coach construction and ship construction.

Method of use:

Shake or stir Q-Line® 690B thoroughly before use. Clean, dry, degrease, dust and remove rust from the surfaces before applying. Q-Line® 690B can be applied with an air-less system using a 2-4 bar air-pressure setting and a 317 tip. For best results, spray at a distance of 20 - 30cm. Depending on the application the product can be thinned with water. Q-Line® 690B can be sprayed haze free and does not drip. Contaminated surfaces and filthy equipment can be simply cleaned in “fresh” condition with hot water.

When you apply Q-Line® 690B, it appears blue and will then dry black. This product is not over paintable. Q-Line® 690B is very effective when used with Q-Line® 290A to produce an underbody duo layer coating.

IMPORTANT

Q-Line® Are manufactured by B.I.G International LTD. Q-Line® products information are based on laboratory tests and practical experience. Since the conditions under which the product is used are often outside the control of B.I.G International LTD, we can only guarantee the product quality, since the result is dependent on the substrate, pre-treatment, temperature, air humidity, application etc. B.I.G International LTD reserves the right, without notice to change the product and the given data.



www.qlinedirect.com

Logistics & Technical: Eagle House | Eagle Park Drive | Warrington | Cheshire | WA2 8JA | United Kingdom
t. +44 (0) 1925 241250 | f. +44 (0) 1925 520210 | e. info@big-internationalgroup.com

