



V.1.4 GB
REV 08-01.2016.

High Performance Cleaners

Q-Line® 760

(For professional use only)

Technical Datasheet



www.qlinedirect.com

Logistics & Technical: Eagle House | Eagle Park Drive | Warrington | Cheshire | WA2 8JA | United Kingdom
t. +44 (0) 1925 241250 | f. +44 (0) 1925 520210 | e. info@big-internationalgroup.com





V.1.4 GB
REV 08-01.2016.

High Performance Cleaners

TDS

Colour/Type	Clear / Strong general alkaline based universal cleaner.
Areas of usage:	De-greasing surfaces, such as the cleaning of trucks, and heavy equipment.
Environment:	Fully Bio-degradable, Please check local requirements and MSDS.
Packaging:	25 litre, IBC 1000 litre
PPE:	Avoid skin contact. Refer to MSDS.
Storage:	Min/Max temp -10/+25
Surface prep:	None
Equipment needed:	High-pressure cleaner with chemical injection system.
Tests:	ISO9001. (For further information contact B.I.G International LTD).
Applying/Drying:	Through high pressure steam system.
Origin/Manufacture:	B.I.G International NV (Netherlands)



www.qlinedirect.com

Logistics & Technical: Eagle House | Eagle Park Drive | Warrington | Cheshire | WA2 8JA | United Kingdom
t. +44 (0) 1925 241250 | f. +44 (0) 1925 520210 | e. info@big-internationalgroup.com





V.1.4 GB
REV 08-01.2016.

High Performance Cleaners

Useful Information

How to optimise the use of Q-Line® 760

Method of use:

The alkaline based universal cleaner contains anti-corrosion VCI particles to prevent aggressive and corrosive characteristics seen in normal cleaners. Also being highly concentrated 1:50 the cleaner is extremely economical to use. Run a solution of 1.0% Q-Line® 760 through your high-pressure system with hot or cold water. Ideally use water temperature settings at approximately 50 – 120 degrees. The product becomes bio-degradable ISO 14855-2 within 28 days.

Pressure setting at approximately 80 – 100 Bars. Clean from the top and downwards. You must leave the solution on the surface for around 5-10 minutes before removing to ensure it cleans effectively. To remove switch off the chemical injection and steam clean off with hot water.

Rinse off with plenty of hot water. Make sure all Q-Line® 760 residue is completely cleaned off.

Please note the product does not foam excessively and the green colouring is present to allow for easy tank level identification purposes only.

IMPORTANT

Q-Line® Are manufactured by B.I.G International LTD. Q-Line® products information are based on laboratory tests and practical experience. Since the conditions under which the product is used are often outside the control of B.I.G International LTD, we can only guarantee the product quality, since the result is dependent on the substrate, pre-treatment, temperature, air humidity, application etc. B.I.G International LTD reserves the right, without notice to change the product and the given data.



www.qlinedirect.com

Logistics & Technical: Eagle House | Eagle Park Drive | Warrington | Cheshire | WA2 8JA | United Kingdom
t. +44 (0) 1925 241250 | f. +44 (0) 1925 520210 | e. info@big-internationalgroup.com

